

AQUA FLO®

Aqua Flo Gen H5 Residential Crossover High Flow Systems

A Security System For Your Water

UV technology provides additional security for your water supply. It is proven to control microbiological (bacteria & virus) issues in water including ***E.coli***, ***Cryptosporidium***, and ***Giardia Lamblia*** without the use of chemicals.

Gen H5 Residential Systems

Features:

- ◆ Five models available (Gen H5-5, 10, 15, 25 & 40)
- ◆ Colour user interface with full diagnostics and warnings including QR codes
- ◆ "Future-proof" expandability port for future upgrades and options
- ◆ Axial flow, 316L stainless steel reactor, polished reactors with integral sensor port to allow for sensor upgradeability in the future (comes standard with visual glow plug)
- ◆ Designed & manufactured to ASME pressure vessel standards
- ◆ Flow rates stated at 95% UVT at a dose of 30mJ/cm²
- ◆ User friendly bayonet style lamp connector (Quick ¼ turn removal. No extra tools required.)
- ◆ True gland seal retaining nut with positive stop
- ◆ Reliable, industry proven low pressure, high-output (LP-HO) coated UV lamps with ceramic bases for durability and a 10,000 hour life
- ◆ Universal input, constant current electronic controller (one controller for all systems) in a splash-proof case
- ◆ Warranty (refer to Owner's Manual for complete details including conditions & exclusions):
 - Reactor Chamber - Ten (10) Year Limited
 - Electronics - Three (3) Year Limited
 - UV Lamps - One (1) Year Limited
 - Quartz Sleeves - One (1) Year Limited

Guidelines for Use

Parameter	Level
Hardness	< 7 gpg (120 mg/L)
Iron (Fe)	< 0.3ppm (mg/L)
Manganese (Mn)	< 0.05ppm (mg/L)
Tannins	< 0.1ppm (mg/L)
Turbidity	< 1 NTU
Transmittance (UVT)	> 75%





AQUA FLO GEN EQUIPMENT SPECIFICATIONS

AQUA FLO GEN H-5, Residential Crossover UV systems, non-monitored

MODEL	GENH5-5 40030010	GENH5-10 40030011	GENH5-15 40030012	GENH5-25 40030013	GENH5-40 40030014
Flow Rate (Industry Standard)	4 GPM 15.1 lpm 0.9 m ³ /hr.	10 GPM 37.9 lpm 2.3 m ³ /hr.	14 GPM 53 lpm 3.2 m ³ /hr.	25 GPM ² 95 lpm 5.7 m ³ /hr.	40 GPM 151 lpm 9.1 m ³ /hr.
Alternate flow @ 16 mJ/cm ² (US Public Health)	8 GPM 30.3 lpm 1.8 m ³ /hr.	19 GPM ¹ 71.9 lpm 4.3 m ³ /hr.	27 GPM ² 102.2 lpm 6.1 m ³ /hr.	47 GPM ² 178 lpm 10.7 m ³ /hr.	78 GPM ³ 295 lpm 17.7 m ³ /hr.
Alternate flow @ 40 mJ/cm ² (NSF/EPA)	3 GPM 11.4 lpm 0.7 m ³ /hr.	7 GPM 26.5 lpm 1.6 m ³ /hr.	11 GPM 41 lpm 2.5 m ³ /hr.	19 GPM 72 lpm 4.3 m ³ /hr.	31 GPM 117 lpm 7 m ³ /hr.
Port Size	½" MNPT	¾" MNPT	1" MNPT	1" MNPT	1½" MNPT
Electrical	90-265V/50-60Hz. (IEC power cords required)				
Power Plug	North American, NEMA 5-15, 3-wire for all 110V				
Lamp Watts	18	34	45	67	101
Power (watts)	20 (19 @ 230V.)	38 (36 @ 230V.)	57 (48 @ 230V.)	73 (72 @ 230V.)	115 (108 @ 230V.)
Replacement Lamp	40040018	40040019	40040020	40040021	40040022
Replacement Sleeve	40040039	40040041	40040042	40040044	40040047
Reactor Dimensions	3.5 x 11.7" (8.9 x 29.8 cm)	3.5 x 16.5" (8.9 x 41.8 cm)	3.5 x 20.0" (8.9 x 50.8 cm)	3.5 x 26.9" (8.9 x 68.3 cm)	3.5 x 40.7" (8.9 x 103.4 cm)
Chamber Material	316L Stainless Steel, A249 Pressure Rated Tubing, Polished & Passivated				
Controller Dimension	8.6 x 4.2 x 3.5" (217.4 x 107.5 x 88.7 mm)				
Operating Pressure	0.7-10.3 bar (10-150 psi)				
Optimum Water Temperature	2-40° C (36-104° F)				
UV Monitor Port (upgradeability)	Yes, includes visual glow plug				
Solenoid Output	Yes, but requires optional solenoid module				
4-20 mA Output	Yes, but requires optional 4-20 mA module				
Lamp Change Reminder (audible & visual)	Yes				
Lamp-Out Indicator (audible & visual)	Yes				
Shipping Weight	4.5 kg. (9.9 lbs.) 4 kg. (8 lbs.) cubed	5.4 kg. (11.9 lbs.) 5 kg. (11 lbs.) cubed	6.0 kg. (13.2 lbs.) 6 kg. (13 lbs.) cubed	7.2 kg. (15.9 lbs.) 8 kg. (16 lbs.) cubed	9.7 kg. (21.4 lbs.) 11 kg. (24 lbs.) cubed
Note: 1. based on flow velocity of 8.2 ft/sec (2.5 m/sec.), flow rate limited to 13.6 gpm (50 lpm) (3.1 m ³ /hr.) for 3/4" port 2. based on flow velocity of 8.2 ft/sec (2.5 m/sec.), flow rate limited to 22.1 gpm (84 lpm) (5.0 m ³ /hr.) for 1" port 3. based on flow velocity of 8.2 ft/sec (2.5 m/sec.), flow rate limited to 52 gpm (197 lpm) (11.8 m ³ /hr.) for 1 ½" port					

Sample Screens



NSF Certified Models Available. Contact Customer Service For Details.

REPLACEMENT PARTS

System	Lamps	Sleeves	Controller
Aqua Flo Gen H5-5	#40040018	#40040039	#40040074
Aqua Flo Gen H5-10	#40040019	#40040041	#40040074
Aqua Flo Gen H5-15	#40040020	#40040042	#40040074
Aqua Flo Gen H5-25	#40040021	#40040044	#40040074
Aqua Flo Gen H5-40	#40040022	#40040047	#40040074

Options



UV Sensor Module
Allows the 254nm UV wavelength to be measured and displayed via the GEN-H5 controller. The sensor plugs directly into the controller and is mounted in the sensor port located on all Gen H5 units.



Solenoid Module
Used to power a remote normally closed solenoid valve (not included). Solenoid valve will close on lamp failure or when low UV conditions are detected by the sensor. Available in 110V MODSOL1 (Item # 40040006)

AQUA FLO®

Your Local Water Specialist